



AAMA PERFORMANCE TESTING RESULTS

MODEL	DESCRIPTION	TEST SIZE	PERFORMANCE CLASS	DESIGN PRESSURE (PSF)	INFILTRATION (CFM/FT)	EXFILTRATION (CFM/FT)	CANADIAN EXFIL / INFIL RATING	WATER PENETRATION (PSF)
3121	Single-slide (XO or OX)	72 X 60	LC-PG 35	35.09	0.04	0.02	A3	5.43
3132	Three-lite slider (XOX)	108 X 66	LC-PG 30	30.08	0.06	0.05	A3	5.43
3221	Single-hung	44 X 75	LC-PG 45	40.10	0.11	0.08	A3	6.90
3242	Twin Single-hung	88 X 75	LC-PG 25	25.06	0.12	0.10	A2	6.06
3010	Picture (Fixed)	55 X 55	LC-PG 70	70.18	0.01	0.01	Fixed	11.28
3310	Picture (Fixed)	55 X 55	LC-PG 55	55.14	0.01	0.01	Fixed	15.04
4722	Double-slide (XX)	72 X 56	LC-PG35	35.09	0.12	0.11	A2	5.43
4622	Double-hung	44 X 75	LC-PG25	45.11	0.19	0.19	A2	8.35
3411	Casement*	32 X 59	CW-PG 85	85.21	0.10	0.11	A2	15.04
3442	Case/Pic/Case OV Pic	108 X 96	LC-PG 25	25.06	0.12	0.12	A2	8.35
3511	Awning	47 X 32	LC-PG 55	55.14	0.17	0.18	A2	15.04
3410	Picture (Fixed)	55 X 55	LC-PG 55	55.14	0.01	0.01	Fixed	15.04
1121	Single-slide (XO or OX)	71 X 55	LC-PG 35	30.09	0.14	0.12	A2	5.43
1221	Single-hung	44 X 75	LC-PG 40	40.10	0.16	0.17	A2	6.06
1010	Picture (Fixed)	55 X 55	LC-PG 55	55.15	0.03	0.03	Fixed	8.36
6221	Single-hung (Triple Glazed)	44 X 75	LC-PG 35	35.09	0.22	0.19	A2	5.43
6121	Single-slide (Triple Glazed)	72 X 60	LC-PG 40	40.10	0.17	0.13	A2	6.06
6310	Picture (Triple Glazed)	55 X 55	LC-PG 70	70.18	0.01	0.02	Fixed	12.11
6310	Picture (Triple Glazed)	75 X 96	LC-PG 25	40.10	0.01	0.02	Fixed	6.06
3821	Patio Door	87 X 87	LC-PG 30	30.08	0.09	0.08	A3	7.52
5821	Patio Door	87 X 87	LC-PG 25	25.06	0.06	0.07	A3	6.90
6821	Patio Door (XO)	96 X 96	LC-PG 35	35.09	0.11	0.10	A2	5.43
6832	Patio Door (XXO)	240 X 120	LC-PG 20	20.05	0.15	0.08	A2	3.13
6842	Patio Door (XXXO)	240 X 120	R-PG 15	15.04	0.11	0.06	A3	3.13

* Please request CW-PG 85 if needed. Standard production Casment is a LC-PG 55

Last Updated 4/24/2025